

## *Advantages of Type 2 Titanium Anodizing*

- Produces anti-galling and wear resistant properties at the surface.
- No introduction of hydrogen or hydrogen embrittlement.
- Increase fatigue strength up to 20% due to the homogeneous surface treatment.
- Coating forms as a penetrating layer rather than growth or “build-up” at the surface, which results in no dimensional change.
- Process may be successfully utilized on both CP and most commercial alloys of titanium.
- Titanium anodize is semi-conductive which allows re-anodization without need for stripping the original coating. Bare or machined areas will “heal” over and be indistinguishable from the original.
- Improvement to surface finish of greater than 50% is attained without special vibratory or burnishing methods.
- As the coating has increased lubricity, in moving parts there are improvements to surface finish, reduction in erosion and abrasion, and the prevention of wear by fretting.
- High strength to weight ratio, good fatigue properties and excellent corrosion resistance.
- Coating is continuous and does not flake off in highly stressed areas.
- Anodize is non-toxic to the human body and fully biocompatible.
- Coating tends to level surface imperfections.
- Titanium anodize is compatible with various aircraft fluids, is not adversely effected by extremes of temperature ranging from -70 to 260 °F and is not effected by humidity or exposure to salt water.
- Titanium anodize is used as a pretreatment for dry film lubricants.
- Titanium anodize can be welded to or over.
- The characteristic gray color of Type 2 anodized titanium is easily distinguishable from stainless steel.



ALUMINUM AND TITANIUM FINISHING AND ANODIZING FOR PROTECTION, WEAR AND APPEARANCE

44 La Porte St.  
Arcadia, CA 91006  
626-445-3303  
Fax: 626-445-3135

1750 Monticello Court  
Ontario, CA 91761  
909-923-0562  
Fax: 909-923-5325

401 W. Rowland  
Santa Ana, CA 92707  
714-557-2411  
Fax: 714-557-0408

2450 Deelyn Dr.  
Warsaw, IN 46580  
574-269-5900  
Fax: 574-269-5966

Visit our web site: [www.danco.net](http://www.danco.net)

*There are other factors which may affect the application of anodized coatings or the base product after anodizing. Please consult with our technical support staff.*